

No	RELEASED BY	LOCKS	NORMAL	LOCKS	BOTH WAYS	RELEASES
WHEEL	1 (G.L.)					2 (G.L.)
1		6.8.9.28.39.	(22W 25N)			WHEEL (G.L.)
2	WHEEL (G.L.)					
3	4.5.6.9.10.					
4	(5.7N ESL)	16		17		3
5	(6N ESL)	17.21.23.		16		3
6	(9N ESL)	1.21.23.				3
7	17.20. (8N ESL)	19.		16		
8	20.21. (9N MSL)	1.19.24.				
9	(10N ESL)	1.24.	(22W 25R)	21.23.25.	(19W 21R)	3
10	(11N ESL)			1		3
11						
12	X					
13	X					
14	X					
15	DETONATOR					
16		4.35.37.				
17		5.	(24W 21R) (26W 25N)			7
18	20	19.21.25.26.				
19		7.8.18.25.				
20				21		7.8.18.
21		5.6.18.23.26.				8 (24)
22	23	24.37. (1W 25N) (9.26W 25R)		25		
23		5.6.21.38. (39 W 29N)				22. (24) 25
24	(21 or 23)	8.9.22.25. (17W 21R) (27W 23R)		1	(19W 21R)	
25	23	18.19.24.				
X	ORIGINAL DRAWN: ISSUED:	ROSSETT LOCKING TABLE				
W	REG No.					S3018 /3/1

No	RELEASED BY	LOCKS NORMAL	LOCKS BOTH WAYS	RELEASES
26		18.21. (17W25N)(22.27W25R)	19.25.	
27		37.38. (24W23R)(26W25R)		35
28	29	1.35.36.39.		
29		38.		28.36.
30			29	36.38.39.
31	DETONATOR			
32	X			
33	X			
34	X			
35	27	16.28.	29.	
36	29.30. (35N MSL)	28.	1.27.	
37		16.22.27.	23.25.	40
38	30 (37N ESL)	23.27.29.	1	40
39	30 (36.38N ESL)	1.28. (23W29N)		40
40	37.38.39.			
	V.T.5 BAR 4" CTRS			
	SHORT LEVERS :	3.4.11.16.17.19.27.35.40.		
#	FOR CONSTRUCTION	OF FRAME (TESTED IN WORKS	17.10.58)	
X	ORIGINAL DRAWN: 20.3.58 *	ROSSETT		
W	TABLE ISSUED: 30.4.58			
	REG No.	LOCKING TABLE		S3018 /3/2